

Primary lithium batteries

Li-SOCl₂ range



Li-SOCl₂ cells

Production site	Size	Open circuit voltage	Nominal voltage	Nominal capacity (drain) (2.0 V cut-off)	Maximum recommended continuous current	Operating temperature range	Outside diameter max.	Height max.	Typical weight	UL recognition	Transport status
-----------------	------	----------------------	-----------------	------------------------------------------	----------------------------------------	-----------------------------	-----------------------	-------------	----------------	----------------	------------------

Small LS/LST/LSX cells

LS 14250	F	1/2 AA	3.67 V	3.6 V	1.2 Ah (1 mA)	35 mA	-60/+ 85°C*	14.65 mm	24.8 mm	8.9 g	yes	Non-restricted
LST 14250	UK	1/2 AA	3.67 V	3.6 V	1.2 Ah (1 mA)	35 mA	-60/+ 85°C*	14.20 mm	25.15 mm	8.8 g	yes	Non-restricted
LS 14250C	F	1/2 AA	3.67 V	3.6 V	1.2 Ah (1 mA)	15 mA	-60/+ 70°C*	14.65 mm	24.8 mm	8.9 g	yes	Non-restricted
LS 14250W	F	1/2 AA	3.67 V	3.6 V	1.2 Ah (1 mA)	35 mA	-60/+ 95°C*	14.65 mm	24.8 mm	8.9 g	—	Non-restricted
LS 14500	F	AA	3.67 V	3.6 V	2.6 Ah (2 mA)	70 mA	-60/+ 85°C*	14.65 mm	50.3 mm	16.7 g	yes	Non-restricted
LST 14500	UK	AA	3.67 V	3.6 V	2.45 Ah (2 mA)	70 mA	-60/+ 85°C*	14.20 mm	49.85 mm	16.3 g	yes	Non-restricted
LS 14500C	F	AA	3.67 V	3.6 V	2.7 Ah (2 mA)	25 mA	-60/+ 70°C*	14.65 mm	50.3 mm	16.2 g	yes	Non-restricted
LS 14500W	F	AA	3.67 V	3.6 V	2.6 Ah (1 mA)	60 mA	-60/+ 95°C*	14.65 mm	50.3 mm	16.2 g	yes	Non-restricted
LSX 14500	F	AA	3.67 V	3.6 V	2.1 Ah (1 mA)	150 mA	-60/+ 85°C*	14.65 mm	50.3 mm	17.5 g	yes	Non-restricted
LST 17330	UK	2/3 A	3.67 V	3.6 V	2.1 Ah (3 mA)	25 mA	-60/+ 85°C*	16.50 mm	33.4 mm	14.4 g	yes	Non-restricted
LS 17500	F	A	3.67 V	3.6 V	3.6 Ah (3 mA)	130 mA	-60/+ 85°C*	17.00 mm	50.9 mm	21.9 g	yes	Non-restricted

*Cells leakproof up to +130°C

Large LS cells

LS 26500	F	C	3.67 V	3.6 V	7.7 Ah (4 mA)	150 mA	-60/+ 85°C*	26.00 mm	49.1 to 50.4 mm***	48 g	yes	Class 9
LS 33600**	F	D	3.67 V	3.6 V	17.0 Ah (5 mA)	250 mA	-60/+ 85°C*	33.40 mm	60.2 to 61.6 mm***	90 g	yes	Class 9
LS 33600C**	F	D	3.67 V	3.6 V	18.5 Ah (1 mA)	80 mA	-60/+ 70°C*	33.40 mm	60.2 to 61.6 mm***	90 g	yes	Class 9

*Cells leakproof up to +120°C

**Low Magnetic cell versions available

*** Depending on cell finish

LSH spiral cells

LSH 26180	F	1/3 C	3.67 V	3.6 V	1.2 Ah (10 mA)	0.4 A	-60/+ 85°C*	26.20 mm	18.6 mm	24 g	—	Non-restricted
LSH 14	F	C	3.67 V	3.6 V	5.8 Ah (15 mA)	1.3 A	-60/+ 85°C*	26.00 mm	50.4 mm	51 g	yes	Class 9
LSH 14 "light"	F	C	3.67 V	3.6 V	3.6 Ah (15 mA)	1.3 A	-60/+ 85°C*	26.00 mm	50.4 mm	51 g	—	Non-restricted
LSH 20**	F	D	3.67 V	3.6 V	13.0 Ah (15 mA)	1.8 A	-60/+ 85°C*	33.40 mm	61.6 mm	100 g	yes	Class 9
LSH 20-150	F	D	3.67 V	3.6 V	14.0 Ah (100 mA)	300 mA	-20/+ 150°C	32.05 mm	61.7 mm	100 g	—	Class 9

* Cells leakproof up to +120°C

**High Temperature (120°C max) LSH 20 HTS cell version available

All LSH cells are fitted with individual 5 Amp fuse protection

Primary cells and batteries are not rechargeable.

Their internal impedance may rise versus time, especially in case of exposure at elevated temperature.



saft

Li-SOCl₂ Military battery packs

	Cell type construction *	Open circuit voltage	Nominal voltage	Voltage cut-off	Rated capacity	Maximum dimensions	Typical weight	Safety features	NATO Stock Number (NSN)	Typical applications
PS 31 A	1s1p LSH 26180	3.67 V	3.6 V	2.0 V	1.2 Ah	26.2 x 18.9 mm	25 g	5 A fuse	6135-14-376-4875	Night vision
PS 38 A	5s1p LSH 26180	18.3 V	17.5 V	10.0 V	1.2 Ah	110.7 x 37 mm	155 g	5 A fuse	6135-14-389-9050	Laser telemetry
PS 40 A	4s1p LSH 14	14.7 V	14.0 V	10.0 V	4.6 Ah	108 x 65 x 49 mm	285 g	PTC 1.1 A**	6135-14-420-1760	Radiocommunication (TRPP 11/13)
PS 42 A	2s1p LSH 20	7.3 V	7.0 V	5.0 V	9.0 Ah	69.9 x 67.2 x 34 mm	230 g	PTC 3.5 A**	6135-14-434-0766	Radiocommunication (TRPP 39)
PS 48 B	5s2p LSH 20	18.3 V	17.5 V	12.6 V	18.0 Ah	212.4 x 72.7 x 68.5 mm	1150 g	PTC 1.85 A**	6135-14-451-7198	Radiocommunication (TRC 350)
PS 52 A	2s1p LSH 20	7.3 V	7.2 V	5.0 V	12.5 Ah	77.5 x 63.5 x 34.6 mm	225 g	PTC 2.0 A**	6135-14-459-9265	Radiocommunication (Portable PR4G)
PS 53 B	6s1p LSH 20	22.0 V	21.0 V	15.0 V	12.5 Ah	210.5 x 68.5 x 37.5 mm	720 g	PTC 2.5 A**	6135-14-459-9266	Radiocommunication (Portable PR4G)

* Xs Yp = Y parallel branches of X cells in series per branch

** Maximum hold current

Li-SOCl₂ Civil battery packs

	Cell type construction *	Open circuit voltage	Nominal voltage	Rated capacity	Maximum dimensions	Typical weight	Typical applications
LS 14250 MLB	1s1p LS 14250	3.67 V	3.6 V	1.2 Ah	16.8 x 28.6 mm	15 g	Metering, professional electronics
LS 9V	3s1p LS 14250	11.0 V	9.0 V	1.2 Ah	49.1 x 46.8 x 26.8 mm	29 g	Memory back-up, metering, smoke detectors, professional electronics
Lithopack	2s1p LS 14500	7.3 V	7.2 V	2.6 Ah	56.6 x 31.6 x 17.3 mm	34 g	Memory back-up, metering, professional electronics

Primary cells and batteries are not rechargeable.

This data sheet is an insert part of the Primary lithium batteries Selector guide (ref 31048-2), where complementary information and data on features, safety and storage can be found.

Saft
Specialty Battery Group
 12, rue Sadi Carnot
 93170 Bagnoleux – France
 Tel.: +33 (0)1 49 93 19 18
 Fax: +33 (0)1 49 93 19 69

www.saftbatteries.com

Doc N° 31049-2-0508
 Edition: May 2008

Data in this document is subject to change without notice and becomes contractual only after written confirmation. Single cells mentioned in this document may have their own specific data sheet with complementary data. Please check website.

Published by the Communications Department.
 Photo credit: Saft.

Société anonyme au capital de 31 944 000 €
 RCS Bobigny B 383 703 873

Produced by Arthur Associates Limited.



SAFT