

Size	Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions W×T×H(mm)	Standard Charge		Rapid Charge		Weight Approx (g)
					Current (mA)	Time (h)	Current (mA)	Time (h)	
7/5F6T	H1200 7/5F6T	1.2	1200	17.0 _{-1.0} ×6.1 _{-0.7} ×76.2 _{-1.0}	120	15	240	6.5	28.0
7/5F6 (LF6)	H1500 7/5F6	1.2	1500	17.0 _{-1.0} ×6.1 _{-0.7} ×76.2 _{-1.0}	150	15	750	2.3	28.5
	H1350 7/5F6C	1.2	1350	17.0 _{-1.0} ×6.1 _{-0.7} ×67.0 _{-1.0}	135	15	675	2.3	26.0
	H1200 7/5F6C	1.2	1200	17.0 _{-1.0} ×6.1 _{-0.7} ×67.0 _{-1.0}	120	15	600	2.3	25.7
	H1200 7/5F6	1.2	1200	17.0 _{-1.0} ×6.1 _{-0.7} ×67.0 _{-1.0}	120	15	600	2.3	26.1
	H1100 7/5F6C	1.2	1100	17.0 _{-1.0} ×6.1 _{-0.7} ×67.0 _{-1.0}	110	15	1100	1.2	25.5
	H1100 7/5F6	1.2	1100	17.0 _{-1.0} ×6.1 _{-0.7} ×67.0 _{-1.0}	110	15	1100	1.2	26.4
	H900 7/5F6C	1.2	900	17.0 _{-1.0} ×6.1 _{-0.7} ×67.0 _{-1.0}	90	15	900	1.2	23.5
	H900 7/5F6	1.2	900	17.0 _{-1.0} ×6.1 _{-0.7} ×67.0 _{-1.0}	90	15	900	1.2	23.5
F6	H700 7/5F6	1.2	700	17.0 _{-1.0} ×6.1 _{-0.7} ×67.0 _{-1.0}	70	15	700	1.2	21.5
	H850F6C	1.2	850	17.0 _{-1.0} ×6.1 _{-0.7} ×48.0 _{-1.0}	85	15	850	1.2	18.5
	H800F6	1.2	800	17.0 _{-1.0} ×6.1 _{-0.7} ×48.0 _{-1.0}	80	15	800	1.2	18.0
	H750F6C	1.2	750	17.0 _{-1.0} ×6.1 _{-0.7} ×48.0 _{-1.0}	75	15	750	1.2	18.5
	H750F6	1.2	750	17.0 _{-1.0} ×6.1 _{-0.7} ×48.0 _{-1.0}	75	15	750	1.2	18.0
	H600F6C	1.2	600	17.0 _{-1.0} ×6.1 _{-0.7} ×48.0 _{-1.0}	60	15	600	1.2	17.0
4/5F6	H600F6	1.2	600	17.0 _{-1.0} ×6.1 _{-0.7} ×48.0 _{-1.0}	60	15	600	1.2	17.0
	H600 4/5F6	1.2	600	17.0 _{-1.0} ×6.0 _{-0.7} ×37.0 _{-1.0}	60	15	600	1.2	13.5
	H520 4/5F6C	1.2	520	17.0 _{-1.0} ×6.0 _{-0.7} ×35.8 _{-1.0}	52	15	520	1.2	13.5
	H520 4/5F6	1.2	520	17.0 _{-1.0} ×6.0 _{-0.7} ×35.8 _{-1.0}	52	15	520	1.2	13.5
	H450 4/5F6C	1.2	450	17.0 _{-1.0} ×6.0 _{-0.7} ×35.8 _{-1.0}	45	15	450	1.2	12.5
	H450 4/5F6	1.2	450	17.0 _{-1.0} ×6.0 _{-0.7} ×35.8 _{-1.0}	45	15	450	1.2	12.5
2/3F6	H400 2/3F6	1.2	400	17.0 _{-1.0} ×6.0 _{-0.7} ×30.0 _{-1.0}	40	15	400	1.2	11.1
3/5F6S	H550 3/5F6S	1.2	550	16.0 _{-1.0} ×6.3 _{-0.7} ×34.0 _{-1.0}	55	15	550	1.2	13.5
	H520 3/5F6S	1.2	520	16.0 _{-1.0} ×6.3 _{-0.7} ×34.0 _{-1.0}	52	15	520	1.2	13.0
	H450 3/5F6S	1.2	450	16.0 _{-1.0} ×6.3 _{-0.7} ×34.0 _{-1.0}	45	15	450	1.2	12.6
LSD 1/3F6S	H160 1/3F6SLSD	1.2	160	14.5 _{-1.0} ×6.0 _{-0.7} ×21.0 _{-1.0}	16	15	80	2.3	6.5
	H180 1/3F6SLSD	1.2	180	14.5 _{-1.0} ×6.0 _{-0.7} ×21.0 _{-1.0}	18	15	90	2.3	6.8
	H200 1/3F6SLSD	1.2	200	14.5 _{-1.0} ×6.0 _{-0.7} ×23.5 _{-1.0}	20	15	100	2.3	7.0
1/3F6S	H160 1/3F6S	1.2	160	14.5 _{-1.0} ×6.3 _{-0.7} ×21.0 _{-1.0}	16	15	160	1.2	6.0
	H180 1/3F6S	1.2	180	14.5 _{-1.0} ×6.3 _{-0.7} ×21.0 _{-1.0}	18	15	180	1.2	6.1
	H200 1/3F6S	1.2	200	14.5 _{-1.0} ×6.3 _{-0.7} ×21.0 _{-1.0}	20	15	200	1.2	6.2
	H220 1/3F6S	1.2	220	14.5 _{-1.0} ×6.3 _{-0.7} ×21.0 _{-1.0}	22	15	220	1.2	6.8
	H280 1/3F6S	1.2	280	14.5 _{-1.0} ×6.3 _{-0.7} ×23.5 _{-1.0}	28	15	140	2.3	7.3
F8	H300 1/3F6S	1.2	300	14.5 _{-1.0} ×6.3 _{-0.7} ×23.5 _{-1.0}	30	15	150	2.3	7.5
	H1200F8C	1.2	1200	17.0 _{-1.0} ×8.2 _{-0.5} ×48.0 _{-1.0}	120	15	600	2.3	24.5
	H1200F8	1.2	1200	17.0 _{-1.0} ×8.2 _{-0.5} ×48.0 _{-1.0}	120	15	600	2.3	24.5
4/5F8	H1100F8	1.2	1100	17.0 _{-1.0} ×8.2 _{-0.5} ×48.0 _{-1.0}	110	15	1100	1.2	24.5
	H850 4/5F8	1.2	850	17.0 _{-1.0} ×8.2 _{-0.5} ×36.0 _{-1.0}	85	15	850	1.2	18.0
	H750 4/5F8	1.2	750	17.0 _{-1.0} ×8.2 _{-0.5} ×36.0 _{-1.0}	75	15	750	1.2	17.5

Note:

- ❖ Nominal Capacity — Minimum discharge capacity when a single cell is discharged at 0.2CmA and 20°C after being charged at 0.1CmA for 16 hours.
- ❖ Typical Capacity — Discharge capacity (for reference only) when a single cell is discharged at 0.2CmA and 20°C after being charged at 0.1CmA for 16 hours.
- ❖ Weight Approximate — For single cell only.
- ❖ C-High Cap (Consumer Head)
- ❖ LSD-Low Self-discharge
- ❖ H-High Temperature