

Sheet1

Lítíum sívalar rafhlöður Li-SOCl₂
(Energy Type)

GB	Model	Nominal Voltage (V)	Dimensions (mm)	Discharge Characteristics(23°C)				Cut-off Voltage (V)	Weight (g)	Operating Temperature (°C)
				Nominal Capacity (mAh)	Standard Current (mA)	Max Discharge Current (mA)				
	IEC					Continuous	Pulse			
ER13150		3.6	13.0×15.0	450	0.5	10	20	2	5.5	-55~+85
ER14250	1/2AA	3.6	14.5×25.0	1200	0.5	50	100	2	10	-55~+85
ER14335	2/3AA	3.6	14.5×33.5	1600	0.7	50	100	2	13	-55~+85
ER14505	AA	3.6	14.5×50.5	2400	1	100	200	2	19	-55~+85
ER18505	A	3.6	18.5×50.5	3500	1	100	200	2	32	-55~+85
ER26500	C	3.6	26.2×50.5	9000	2	200	400	2	55	-55~+85
ER10280		3.6	10.0×28.0	450	0.5	10	20	2	5	-55~+85
ER10450	AAA	3.6	10.0×45.0	700	1	10	20	2	9	-55~+85
ER34615	D	3.6	34.2×61.5	19000	3	200	400	2	107	-55~+85